# Patron PLUS

MADE IN	
MADEIN	

The Patron PLUS was developed specifically to withstand heavy loads in applications such as motor winches. Dirt, climatic influences, heavy loads, and dimensional stability requirements place high demands on a rope. When designing Patron PLUS, we focused on making it extremely robust and compact.

### Features

- High-quality nylon
- High breaking loads compared with extra light weight
- Robust and compact Protection against
- abrasion and ingress of dirt
- Soft handling
- High comfort in transport and storage

- 11.0mm certified with
  - CT Easy Speed and SKR2 according to EN353-2 11.0mm certified with
  - CTSparrow 200R according to EN341-2A

Core:	Nylon
Cover:	Nylon
Standard:	EN 1891 A
Braid:	32

**Specifications** 







#### CE test results per EN 1891

ø		Weight		Shrinkage	Elongation	Elongation Min. breaking strength						Cover
					50-150 kg	Free leng	Free length With figure 8 knot		Sewn			
mm	inch	g/m	lbs/100'	%	%	daN	lbf	daN	lbf	daN	lbf	%
11.0	7/16	75.0	5.04	4.0	3.0	3,300	7,415	1,900	4,270	2,700	6,065	36.0

## Chameleon 🧭





The new Chameleon is a robust, all-round rope with an ecological footprint. For its production, high-quality yarns left over during color change in the extrusion process is used. Therefore the rope's color is flexible and changes based on the raw material provided. This upcycling helps to reduce waste in the fiber production process. The Chameleon range offers the same great handling and strength you would expect from Teufelberger ropes.

### Features

- All-round rope
- · Robust and long-lasting
- Ecological footprint
- Flexible colors

All diameters Example color

## Specifications

Core:	Nylon			
Cover:	Nylon			
Standard:	EN 1891 A			
Braid:	32			





#### CE test results per EN 1891

Ø		Weight		Shrinkage	Elongation 50-150 kg	Min. breaking strength Free length With figure 8 knot Sewn						Cover
mm	inch	g/m	lbs/100'	%	%	daN	lbf	daN	lbf	daN	lbf	%
10.5	13/32	72.0	4.84	4.0	3.0	3,200	7,190	1,800	4,045	2,600	5,840	37.0
11.0	7/16	75.0	5.04	4.0	3.0	3,300	7,415	1,800	4,045	2,700	6,065	36.0